

Wultson by Tamex Marketing LTD -

Ha-Mashbir St 12, Holon 5885616, Israel

WSON-D INDUSTRIAL SERIES

The new Wultson D units are available in 7 different sizes ranging from 53 liters to 360 liters.

Digital high quality ultrasonic cleaner with a powerful ultrasonic effect . Suitable for many tasks and to clean complex parts.



Very high degrees of cleaning can be achieved in Wultson's ultrasonic cleaners with a proper cleaning liquid.

FEATURES



Digital display.



Die Casting stainless-steel construction.



Including basket and lid.



Setting of time 99-0 min.



Setting of temperature up to 80 °C.



Powerful 40 KHz Ultrasonic effect.

CERTIFICATE OF COMPLIANCE



SPECIFICATIONS

Model No.	Capacity	Transducers	Ultrasonic Power	Frequency	Heating Power	Drainage	Time Range (min)	Temp.(°C)	Tank size (mm)	Basket Size (mm)
WSON530-D	53L	18	0~900W	28/40kHz	3000W	Yes	1~99	30~80	470*320*280	500*350*300
WSON880-D	88L	24	0~1200W	28/40kHz	3000W	Yes	1~99	30~80	550*400*400	530*380*380
WSON990-D	99L	30	0~1500W	28/40kHz	3000W	Yes	1~99	30~80	550*450*400	530*430*380
WSON1350-D	135L	36	0~1800W	28/40kHz	5000W	Yes	1~99	30~80	600*500*450	580*480*430
WSON1750-D	175L	54	0~2700W	28/40kHz	6000W	Yes	1~99	30~80	700*500*500	680*470*480
WSON2640-D	264L	60	1500~3000W	28/40kHz	6000W	Yes	1~99	30~80	800*600*550	780*570*530
WSON3600-D	360L	84	2100~4200W	28/40kHz	9000W	Yes	1~99	30~80	1000*600*600	980*580*580



WSON-D INDUSTRIAL SERIES

CLEANING LIQUIDS

Type	WS PRO 125 Universal	WS PRO 1307	WS PRO 1130
ph value at 20 C°	9.1+-0.3	11.6+-0.3	12.2+-0.3
Gold	++	+	
Silver	++	+	
Cooper/Brass	++	+	~
Aluminium	++	++	
Steel/Iron	+	+	++
Stainless steel	++	++	++
Zinc	++	+	
PVDF/PP/PE	++	++	+
PVC	++	++	
Ceramics	++	++	+
Glass	++	++	+



In addition, further material incompatibilities cannot be excluded. Therefore, test the product on an unimportant spot before its definite use.

++ = Very suited/high
 + = Suitable/average
 ~ = Conditionally/less
 Empty = Not suited



W U L T S O N

Wultson by Tamex Marketing LTD

Ha-Mashbir St 12, Holon 5885616, Israel

www.tamex.co.il | info@tamex.co.il

+972-3-559-4779